

WHEEL ASSEMBLIES



Pivot Walker

ITEM # 8073425001

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, NPT, 11.2X38, NON PNEUMATIC, NON DIRECTIONAL, 10X38 UNIVERSAL STANDARD RIM, 8 HOLE, GALV, STEM GUARD

Pivot Walker Assy Diameter	42.75in
HUB—8 / 9—Hole	36.5in
Tire Pad	13" x 19"
Pivot Shaft	1" DIA x 9.56" LG
Cotter Pin	1/4" x 2"
Caplug	WW-13
Max Weight Capacity	5000 lbs.



11.2 x 38 6 Ply

ITEM # 8073101002

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, 11.2X38, R1, 6 PLY, WITH TUBE, 10X38 UNIVERSAL REINFORCED RIM, 8 HOLE, GALV, STEM GUARD

Tire Width	11.2
Rim Nominal ID	38
Tire Circumference	179in
Ply rating/ Cord material	6PLY/ nylon
Lug number	42
Side Wall Thickness	0.3in
Tread Thickness	1.5in
Tread Shoulder Thickness	1.65in
Depth of lugs	1in
Air Pressure	26psi
Load Rating	2530IBS
Tire Only Weight (lbs)	91lbs.



11.2 x 38 10 Ply

ITEM # 8073101005

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, 11.2X38, R1, 10 PLY, WITH TUBE, 10X38 UNIVERSAL REINFORCED RIM, 8 HOLE, GALV, STEM GUARD

Tire Width	11
Rim Nominal ID	38
Tire Circumference	190in
Ply rating/ Cord material	10PLY/ nylon
Lug number	52
Side Wall Thickness	0.3in
Tread Thickness	1.8in
Tread Shoulder Thickness	2.19in
Depth of lugs	1.25in
Air Pressure	29psi
Load Rating	3784IBS
Tire Only Weight (lbs)	134lbs.



11.2 x 38 Non-Directional

ITEM # 8073101111

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, ND, 11.2X38, 10 PLY, WITH TUBE, 10X38 UNIVERSAL REINFORCED RIM, 8 HOLE, GALV, STEM GUARD

Tire Width	11.2
Rim Nominal ID	38
Tire Circumference	178in
Ply rating/ Cord material	10PLY/ nylon
Lug number	44
Side Wall Thickness	0.3in
Tread Thickness	1.9in
Tread Shoulder Thickness	2.28in
Depth of lugs	1.25in
Air Pressure	24psi
Load Rating	4000 IBS
Tire Only Weight (lbs)	125lbs



11.2 x 24 6 Ply

ITEM # 8073101001

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, 11.2X24, R1, 6 PLY, WITH TUBE, 8X24 UNIVERSAL RIM, 8 HOLE, GALV.

Tire Width	14.9
Rim Nominal ID	24
Tire Circumference	157in
Ply rating/ Cord material	6PLY/ nylon
Lug number	34
Side Wall Thickness	0.3in
Tread Thickness	1.5in
Tread Shoulder Thickness	1.87in
Depth of lugs	1in
Air Pressure	20psi
Load Rating	3322IBS
Tire Only Weight (lbs)	144lbs



14.9 x 24 8 Ply

ITEM # 8073101003

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, 14.9X24, R1, 6 PLY, WITH TUBE, 10X24 UNIVERSAL RIM, 8 HOLE, GALV

Tire Width	11.2
Rim Nominal ID	24
Tire Circumference	136in
Ply rating/ Cord material	8ply/nylon
Lug number	38
Side Wall Thickness	0.3in
Tread Thickness	1.8in
Tread Shoulder Thickness	2.19in
Depth of lugs	1.25in
Air Pressure	35psi
Load Rating	2695IBS
Tire Only Weight (lbs)	80lbs.



Non-Pneumatic Tire

ITEM #

DESCRIPTION

WHEEL ASSEMBLY, Irri-Gator, NPT, 11.2X38, NON PNEUMATIC, 10X38 UNIVERSAL RIM, 8 HOLE, GALV, STEM GUARD

Tire Width	12
Rim Nominal ID	38
Tire Circumference	186in
Ply rating/ Cord material	N/A
Lug number	16
Side Wall Thickness	N/A
Tread Thickness	?
Tread Shoulder Thickness	N/A
Depth of lugs	1.75
Air Pressure	N/A
Load Rating	
Tire Only Weight (lbs)	144lbs

Contact your local Irrigation Components branch today!